

Manufacturing Fine Doors Since 1972

## **Door Frame Price List**

Frames are knock down, u-channel like to wrap around your wall (or butt into a 12" block wall)

July 2004 – **Prices Subject to Change** without notice.

	Paint Oak Maple Cherry Mahogany HM					
		Oak	Maple	Cherry	Manogany	111/1
TI 4 2 M II 4 M 1099	Grade					
Up to 3x7, wall 4-7/8"						
No rating MDF		230	245	300	245	145
20min MDF		245	260	310	260	145
45min MDF		480	529	571	529	145
90min MDF		750	785	840	785	145
Solid Wood **	215				525	
Solid 1100d	-10				020	
Up to 6x7, wall 4-7/8"						
No rating		270	280	330	280	165
20min		278	285	345	285	165
45min		n/a	n/a	n/a	n/a	165
**90min		873	936	965	936	165
9011111		0/3	930	903	930	103
TI / 2 0 II / #/019						
Up to 3x9, wall 4-7/8"						
No rating		280	305	335	305	165
20min		285	315	345	315	165
45min		573	422	775	422	165
90min		985	1030	1050	1030	165
Solid Wood **	290				650	
Up to 6x9, wall 4-7/8"						
No rating		306	315	381	315	180
20min		315	322	388	322	180
45min		n/a	n/a	n/a	n/a	190
**90min		600	1090	1120	1090	190
Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z		000	1070	1120	1070	170

<sup>\*\*</sup>For Hollyman Frames, 90 Minute pairs, there is limited use.

## To order, specify

- Quantity
- Material choice (Wood Type or Hollow Metal)
- Handing, (RH or LH)
- Wall thickness, (usually 4-7/8"for fire-rating, 3-1/2" studs, 5/8" drywall 2 sides)
- Size & specify whether you are writing inside frame rebate size or door size, (if you fail to specify which size you are giving, and write 36x84, we assume this is frame rebate size, for door size of 35-13/16 x 83-1/8")
- Fire-rating (20 / 45/ 60 / 90 minute)
- if ordering door as well, specify requested undercut (ie ½ / ¾" / 3/8") or actual door size
- if door closer prep is req'd (yes / no)
- whether wall is built yet / will; be built to suit if built, give rough opening size.
- If stud is metal or wood (proper attachments are provided

## **Standard Features**

- ASA Strike prep is standard, advise if not wanted
- Prep for 4-1/2"x 4" template hinges with steel reinforcement

For Solid Wood Frame, prep would be hinge only, no latch unless sample provided, we include ¾ x 4-7/8" jamb, doorstop, ¾ x 3-1/2" casing, kwikfit for door.