



## Limitations in fire doors

	<b>20 Minute:</b>	<b>45 Minute:</b>	<b>60 &amp; 90 Minute</b>
<b>Glass Allowances</b>	<ul style="list-style-type: none"> <li><input type="checkbox"/> 1200 sq. Inches -</li> <li><input type="checkbox"/> Max. Lite Size is 40" HIGH</li> <li><input type="checkbox"/> 9-3/8" stiles on lock side (clear lock hole by 5-1/2")</li> <li><input type="checkbox"/> 5-1/2" top &amp; hinge side, 9-10" lock side</li> </ul>	<ul style="list-style-type: none"> <li><input type="checkbox"/> 1296 sq. Inches –</li> <li><input type="checkbox"/> Max. Lite Size allowed is 10x54" (6-8 WEEKS), approx \$300 per lite.</li> <li><input type="checkbox"/> Quick Delivery Size options: 5x35, 6x36, 18x32, would need 10" lock side, min 6" hinge side, approx \$150 per lite (supply of lite kit &amp; cut-out)</li> <li><input type="checkbox"/> 9-3/8" stiles on lock side (clear lock hole by 5-1/2")</li> <li><input type="checkbox"/> 5-1/2" top &amp; hinge side, 9-10" lock side</li> </ul>	<p><b>60 Minute:</b> 100 Sq. Inches – Max. Lite Size is 10x10 or 3x33 or 5x20</p> <p><b>90 Minute:</b> 100 Sq. Inches – Max. Lite Size is 10x10 or 3x33 or 5x20</p>
<b>Pairs</b>	Must have astragal		
<b>Transoms</b>	Must have Steel Transom Bar or Rabet Joint.	Must have Steel Transom Bar or Rabet Joint.	Must have Steel Transom Bar or Rabet Joint.
<b>Maximum Door Size</b>	<ul style="list-style-type: none"> <li><input type="checkbox"/> Plastic Laminate Faced Doors: any rating max size = 4' x 10'</li> <li><input type="checkbox"/> Plastic Laminate Faced Doors pairs max size = 8'x8'</li> <li><input type="checkbox"/> Veneer Faced Doors, 45 min + max size = 4x8'</li> <li><input type="checkbox"/> Veneer Faced Doors with transom max size = 3'6" x 10' (rabetted)</li> </ul>		
<b>Applied Mouldings</b>	Allowed to cover 20% of the door area (no more) Must apply with combination of ULC Listed glue & nails that do not penetrate more than 3/4"		
<b>Location of Lites</b>	Note: <b>Distance Between Glass &amp; door edge / any hardware cut-out: 5-1/2"</b> <ul style="list-style-type: none"> <li>– 9-3/8" stiles on lock side (clear lock hole by 5-1/2")</li> <li>– 5-1/2" top &amp; hinge side, 9-10" lock side</li> <li>– pairs not allowed!!</li> </ul>		

This is meant to be a helpful guideline, your door request will be reviewed for compliance once faxed in to 416-780-9822.